



*designed for today*



**Product: Sub Cable 91**  
**Audio Cable, 2 Conductor**

Cross sec Area	No of Strands	Cond. Type	Insulation Type	Filler
0.12 sqmm	19	ABC	PE	Moisture

Shield	Over all Dia	DCR AT 20 °C	ConductorShield	Capacitance	Conductor Shield
70 % ATC Spiral	6.00 mm	97.0 Ω / KM	32.0Ω / KM	28 PF / Feet	67 Pf / feet

© 2021 Tono Systems

All Rights Reserved.

Although Tono makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Tono provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Tono be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Tono has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Tono products are subject to Tono's standard terms and conditions of sale.

Tono believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Tono's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality special.